



4018 Supercardioid Tabletop Microphone

TABLE OF CONTENTS


Specifications - 4018-D	1
-------------------------	---

Specifications - 4018-D


Directional pattern	Supercardioid
Principle of operation	Pressure gradient
Cartridge type	Pre-polarized condenser
Frequency response	20 Hz - 20 kHz

Effective frequency range, ±2 dB, at 30 cm (11.8 in)	40 Hz - 18 kHz
Sensitivity, nominal, ±2 dB at 1 kHz	12 mV/Pa; -38.4 dB re. 1 V/Pa
Equivalent noise level, A-weighted	Typ. 16 dB(A) re. 20 µPa (max. 19 dB(A))
Equivalent noise level, ITU-R BS.468-4	Typ. 23 dB (max. 26 dB)
Distortion, THD < 1%	134 dB SPL RMS, 137 dB SPL peak
Dynamic range	Typ. 121 dB
Max. SPL, THD 10%	156 dB SPL peak
Switchable attenuator, filters etc.	0 dB / -20 dB
Rated output impedance	200 Ω
Minimum load impedance	2 kΩ
Cable drive capability	100 m (328 ft)
Output balance principle	Impedance balancing with Active Drive
Common mode rejection ratio (CMRR)	> 60 dB
Power supply (for full performance)	P48 (Phantom Power)
Current consumption	2.8 mA
Connector	XLR-3M. Pin 1: shield, Pin 2: signal + phase, Pin 3: - phase
Color	Matte black
Weight	158 g (5.6 oz)
Microphone diameter	19 mm (0.75 in)
Capsule diameter	19 mm (0.75 in)
Microphone length	170 mm (6.7 in)

Maximum output voltage, RMS	8 V
Polarity	+V at pin 2 for positive sound pressure
Temperature range	-40°C to 45°C (-40°F to 113°F)
Relative humidity (RH)	Up to 90%
Matching tolerance (frequency response and sensitivity)	±1 dB
Phase deviation for kit	< 10°



Typical on and off-axis response of DPA 4018



Typical directional characteristics of DPA 4018